

Blocs Creux

|   | CARACTERISTIQUES | | | | | TYPES D'OUVRAGES | | | | | |
|---|------------------|---------------|---------------|----------------|---------------|------------------|---------|---------------------------|--------------------------------|----------|-------------------|
| | Longueur mm | Largeur mm | Hauteur mm | Poids unité | Nb palette | Façades | Refends | soubassements enterrés | Murs séparatifs de logement | cloisons | Rives de plancher |
| 500X45X200 | 500 | 45 | 200 | 8 | 180 | | | | | ☺ | ☺ |
| 500X75X200 | 500 | 75 | 200 | 8 | 144* | | | | | ☺ | |
| 500X100X200 | 500 | 100 | 200 | 9 | 120* | | | | | ☺ | |
| 500X150X200 1 LAME | 500 | 150 | 200 | 11 | 98 | | ☺ | | | | |
| 500X150X200 2 LAMES | 500 | 150 | 200 | 13 | 84 | | ☺ | | | | |
| 500X200X200 40 BARS | 500 | 200 | 200 | 15 | 70* | ☺ | ☺ | ☺ | | | |
| 500X200X200 60 BARS | 500 | 200 | 200 | 15 | 70 | ☺ | ☺ | ☺ | | | |
| 500X150X250 | 500 | 150 | 250 | 18 | 70 | | ☺ | | | | |
| 500X250X200 | 500 | 250 | 200 | 21 | 56 | ☺ | ☺ | ☺ | | | |
| 500X275X200 | 500 | 275 | 200 | 22 | 48 | ☺ | ☺ | ☺ | | | |
| 500X200X200 À EMBOITEMENT | 500 | 200 | 200 | 16 | 70 | ☺ | ☺ | ☺ | | | |
| 500X200X250 À EMBOITEMENT | 500 | 200 | 250 | 21 | 60* | ☺ | ☺ | ☺ | | | |

* peut varier selon l'usine

☺ Type d'ouvrage approprié

SEAC
une équipe en béton un moral d'acier